

# Alcedo HLP 46

## Performance Claims

ISO HM

DIN 51524/2; AFNOR NFE 48-603



## Description

High-efficient hydraulic oil. Intended to be used in high-pressure hydraulic systems operating under medium and heavy conditions. Applicable in mobile and industrial equipment following DIN 51524.

## Advantages

- Enhanced anti-wear characteristics
- Excellent deaerating and demulsifying properties
- Efficient oxidation and rust protection

## Typical characteristics

PROPERTIES	METHOD	UNITS	TYPICAL INDICATORS
Density at 15°C	ASTM D4052	kg/m <sup>3</sup>	876
Viscosity at 40°C	ASTM D7042	cSt	45
Viscosity at 100°C	ASTM D7042	cSt	6,8
Viscosity index	ASTM D227		105
Flash point COC	ASTM D92	°C	218
Pour point	ASTM D97	°C	-36

## Packaging

VOLUME	ART N <sup>o</sup>
20 L	0079
208 L	0080

TOR LUBRICANTS NORWAY  
Fjordalléen 16, 0250 Oslo, Norway  
Phone: +47 852 90054  
E-mail: [info@nordkapp-oil.com](mailto:info@nordkapp-oil.com)

Information in this data sheet believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is given as a guide only. It is the responsibility of the user to evaluate and use products safely. No responsibility is taken for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. You should consult our local representative if you require any further information.