

Alcedo HVLP 46

Performance Claims

ISO HV

DIN 51524/3; ISO 11158 (HV); AFNOR NF E 48-603 (HV)



Description

High-efficient hydraulic oil. Intended to be used in high-pressure hydraulic systems operating under medium and heavy conditions. Applicable in mobile and industrial equipment following DIN 51524/3.

Advantages

- Enhanced anti-wear characteristics
- Excellent deaerating and demulsifying properties
- Efficient oxidation and rust protection

Typical characteristics

PROPERTIES	METHOD	UNITS	TYPICAL INDICATORS
Density at 15 °C	ASTM D4052	kg/m ³	876
Viscosity at 40 °C, not less than	ASTM D7042	cSt	13,5
Ash content, not more than	ASTM D7042	cSt	0,3
Viscosity index, not less than	ASTM D227		115
Flash point COC, not less than	ASTM D92	°C	190
Pour point, not higher than	ASTM D97	°C	-36
Acid number, KOH/g, no more than	ASTM D974	mg	1,5

Packaging

VOLUME	ART №
20 L	0154
208 L	0155

TOR LUBRICANTS NORWAY
Fjordalléen 16, 0250 Oslo, Norway
Phone: +47 852 90054
E-mail: info@nordkapp-oil.com

Information in this data sheet believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is given as a guide only. It is the responsibility of the user to evaluate and use products safely. No responsibility is taken for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. You should consult our local representative if you require any further information.