

Ardena 30

Performance Claims

SAE 30
API CC



Description

High-viscosity engine oil is recommended for use in both diesel and petrol engines with or without turbochargers.

Advantages

- High-performance single-grade engine oil
- High viscosity index
- High dirt dispensing capacity
- Stable lubricant film
- Excellent cleaning capacity
- High thermal stability
- Excellent wear and corrosion protection

Typical characteristics

Packaging

PROPERTIES

Density at 15°C
Viscosity at 100°C
Viscosity index
Flash point COC
Pour point
TBN

METHOD

ASTM D1298
ASTM D445
ASTM D2270
ASTM D92
ASTM D97
ASTM D4739

UNITS

kg/m³
cSt
°C
°C
mgKOH/g

TYPICAL INDICATORS

889
14,9
91
230
-30
8,5

VOLUME

20 L
208 L

ART Nr:

0144
0143

TOR LUBRICANTS NORWAY
Fjordalléen 16, 0250 Oslo, Norway
Phone: +47 852 90054
E-mail: info@nordkapp-oil.com

Information in this data sheet believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is given as a guide only. It is the responsibility of the user to evaluate and use products safely. No responsibility is taken for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. You should consult our local representative if you require any further information.