

Ardena HD 40

Performance Claims

SAE 40
API CF
ACEA E2

MB 228.3, MAN 270, MTU TYPE 1



Description

High-viscosity engine oil is recommended for use in both diesel and petrol engines with or without turbochargers, such as commercial diesel vehicle engines, construction machinery, and agricultural units.

Advantages

- High-performance single-grade engine oil
- High viscosity index
- High dirt dispensing capacity
- Stable lubricant film
- Excellent cleaning capacity
- High thermal stability
- Excellent wear and corrosion protection

Typical characteristics

PROPERTIES	METHOD	UNITS	TYPICAL INDICATORS
Density at 15°C	ASTM D1298	kg/m ³	889
Viscosity at 100°C	ASTM D445	cSt	14,9
Viscosity index	ASTM D2270		91
Flash point COC	ASTM D92	°C	230
Pour point	ASTM D97	°C	-30
TBN	ASTM D4739	mgKOH/g	8,5

Packaging

VOLUME	ART N ^o
20 L	0083

TOR LUBRICANTS NORWAY
Fjordalléen 16, 0250 Oslo, Norway
Phone: +47 852 90054
E-mail: info@nordkapp-oil.com

Information in this data sheet believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is given as a guide only. It is the responsibility of the user to evaluate and use products safely. No responsibility is taken for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. You should consult our local representative if you require any further information.