

Ardena HD 50

Performance Claims

SAE 50
API CF
ACEA E2

MB 228.3, MAN 270, MTU TYPE 1



Description

Super high viscosity engine oil SAE 50 grade is recommended for diesel and petrol engines with or without turbochargers. It can also be used in hydraulic systems, clutches, and gearboxes that require high-performance single-grade engine oil.

Advantages

- High-performance single-grade engine oil
- High viscosity index
- High dirt dispensing capacity
- Stable lubricant film
- Excellent cleaning capacity
- High thermal stability
- Excellent wear and corrosion protection

Typical characteristics

PROPERTIES	METHOD	UNITS	TYPICAL INDICATORS
Density at 15°C	ASTM D1298	kg/m ³	891
Viscosity at 100°C	ASTM D445	cSt	19,1
Viscosity index	ASTM D2270		92
Flash point COC	ASTM D92	°C	232
Pour point	ASTM D97	°C	-28
TBN	ASTM D4739	mgKOH/g	8,4

Packaging

VOLUME	ART N ^o
20 L	0084

TOR LUBRICANTS NORWAY
Fjordalléen 16, 0250 Oslo, Norway
Phone: +47 852 90054
E-mail: info@nordkapp-oil.com

Information in this data sheet believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is given as a guide only. It is the responsibility of the user to evaluate and use products safely. No responsibility is taken for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. You should consult our local representative if you require any further information.