

# Ardena HD 60

## Performance Claims

SAE 60  
API CF  
ACEA E2

MB 228.3, MAN 270, MTU TYPE 1



## Description

Extra viscosity engine oil SAE 60 is suitable for diesel and petrol engines (with or without turbochargers), commercial diesel vehicles, construction machinery, and agricultural units.

## Advantages

- High-performance single-grade engine oil
- High viscosity index
- High dirt dispensing capacity
- Stable lubricant film
- Excellent cleaning capacity
- High thermal stability
- Excellent wear and corrosion protection

## Typical characteristics

PROPERTIES	METHOD	UNITS	TYPICAL INDICATORS
Density at 15°C	ASTM D1298	kg/m <sup>3</sup>	893
Viscosity at 100°C	ASTM D445	cSt	24,2
Viscosity index	ASTM D2270		89
Flash point COC	ASTM D92	°C	240
Pour point	ASTM D97	°C	-25
TBN	ASTM D4739	mgKOH/g	8,6

## Packaging

VOLUME	ART N <sup>o</sup>
20 L	0085

TOR LUBRICANTS NORWAY  
Fjordalléen 16, 0250 Oslo, Norway  
Phone: +47 852 90054  
E-mail: [info@nordkapp-oil.com](mailto:info@nordkapp-oil.com)

Information in this data sheet believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is given as a guide only. It is the responsibility of the user to evaluate and use products safely. No responsibility is taken for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. You should consult our local representative if you require any further information.