

# ATF A

## Performance Claims

### ATF A

GM DEXRON IID | FORD MERCON Conforms: MB 236.8 | MAN 339 L1 | MAN 339 Z2 (D) ZF000697 | ZF TE-ML 04D, 14B, 16L | AS000697 Bosch TE-ML 09X | Voith H55.6335.xx, H55.6336.xx | Renk Doromat | Allison C4 Caterpillar TO-2 | MAN 339 V2



## Description

Multigrade, highly efficient power fluid ensures excellent anti-friction and extreme pressure properties for transmissions. Protects the mechanisms' details out of negative factors during heavy-duty conditions, and reduces the level of energy losses in friction, noise decrease, vibration, and shock load.

## Advantages

- High thermal and oxidative stability
- Perfect wear protection
- Good foam properties
- High viscosity performance in wide temperature range
- Compatibility with sealants

## Typical characteristics

PROPERTIES	METHOD	UNITS	TYPICAL INDICATORS
Density at 15°C	ASTM D1298	kg/m <sup>3</sup>	886
Viscosity at 40°C	ASTM D5293	cSt	43,3
Viscosity at 100°C	ASTM D445	cSt	7,9
Viscosity index	ASTM D2270		156
Flash point COC	ASTM D92	°C	217
Pour point	ASTM D97	°C	-45

## Packaging

VOLUME	ART №
1 L	0134

TOR LUBRICANTS NORWAY  
Fjordalléen 16, 0250 Oslo, Norway  
Phone: +47 852 90054  
E-mail: info@nordkapp-oil.com

Information in this data sheet believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is given as a guide only. It is the responsibility of the user to evaluate and use products safely. No responsibility is taken for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. You should consult our local representative if you require any further information.