

ATF II

Performance Claims

ATF II D

GM Dexron II E-25300; Ford Mercon (M93-1288); MB 236.8; MAN 339 L1; MAN 339 Z2 (D); ZF000697: ZF TE-ML 04D, 14B, 16L; AS000697: Bosch TE-ML 09X; Voith H55.6335.xx, H55.6336.xx; Renk Doromat; Allison C4; Caterpillar TO-2; MAN 339 V2



Description

Special transmission fluid for automatic transmissions and power steering. Used in passenger cars, heavy-duty vehicles, buses, and commercial vehicles, where GM DEXRON II is required.

Advantages

- High thermal and oxidative stability
- Perfect wear protection
- Good foam properties
- High viscosity performance in wide temperature range
- Compatibility with sealants

Typical characteristics

PROPERTIES	METHOD	UNITS	TYPICAL INDICATORS
Density at 15°C	ASTM D1298	kg/m ³	866
Viscosity at 40°C	ASTM D5293	cSt	43,3
Viscosity at 100°C	ASTM D445	cSt	7,9
Viscosity index	ASTM D2270		156
Flash point COC	ASTM D92	°C	217
Pour point	ASTM D97	°C	-45

Packaging

VOLUME	ART №
1 L	0072

TOR LUBRICANTS NORWAY
Fjordalléen 16, 0250 Oslo, Norway
Phone: +47 852 90054
E-mail: info@nordkapp-oil.com

Information in this data sheet believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is given as a guide only. It is the responsibility of the user to evaluate and use products safely. No responsibility is taken for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. You should consult our local representative if you require any further information.