

Aves 5W-40

Performance Claims

SAE 5W-40
API SN/CF
ACEA A3/B4

VW 502.00, 505.00; MB 229.5;
BMW Longlife-01; PORSCHE A40;
Renault RN0700 RN0710; GM-LL-B-025;
PSA B71 2296



Description

Synthetic fuel-efficient engine oil for high-tech petrol and diesel engines in passenger cars and vans. Compatible with turbocharged engines, direct fuel injection, and catalysts. Meets Euro 4 and Euro 5 environmental requirements.

Advantages

- Excellent cold start performance and perfect viscosity temperature behaviour
- Perfect engine protection against wear
- Reduces fuel consumption
- Exceptional engine cleanliness and high corrosion resistance
- Low evaporation

Typical characteristics

PROPERTIES	METHOD	UNITS	TYPICAL INDICATORS
Density at 15°C	ASTM D1298	kg/m ³	856
Viscosity at -30°C	ASTM D5293	cP	5410
Viscosity at 40°C	ASTM D445	cSt	88,4
Viscosity at 100°C	ASTM D445	cSt	14
Viscosity index	ASTM D2270		174
Flash point COC	ASTM D92	°C	232
Pour point	ASTM D97	°C	-40
TBN	ASTM D4739	mgKOH/g	10
Sulphate ashes	ASTM D874	%	1,29

Packaging

VOLUME	ART №
1 L	0008
4 L	0009

TOR LUBRICANTS NORWAY
Fjordalléen 16, 0250 Oslo, Norway
Phone: +47 852 90054
E-mail: info@nordkapp-oil.com

Information in this data sheet believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is given as a guide only. It is the responsibility of the user to evaluate and use products safely. No responsibility is taken for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. You should consult our local representative if you require any further information.