

# Aves 0W-16

## Performance Claims

SAE 0W-16  
API SP/SN Plus

ILSAC GF-5/-6B, Ford, GM, Chrysler, Toyota, Lexus, KIA, Honda,  
Nissan, Mitsubishi, Subaru, Suzuki



## Description

High-performance fully synthetic engine oil specially developed for American and Asian petrol engines of passenger cars, delivery vans, and hybrids. Minimizes the risk of Low-Speed Pre-Ignition in modern engines with GDI and TGDI. Ensures excellent low-temperature flow characteristics to provide optimum protection for the engine at the cold start phase. Withstands extreme loads and safely handles high temperatures under all operating conditions.

## Advantages

- **Optimal engine protection:** Protects against wear, sludge, and corrosion.
- **Enhanced fuel efficiency:** Reduces fuel consumption.
- **Superior cold-start performance:** Ensures quick and reliable starts in cold weather.
- **Extended engine life:** Prolongs engine life with superior wear protection.
- **Formulated for modern engines:** Compatible with a wide range of gasoline engines.

## Typical characteristics

PROPERTIES	METHOD	UNITS	TYPICAL INDICATORS
Density at 20 °C	ASTM D1298	kg/m <sup>3</sup>	870
Viscosity at -35 °C	ASTM D5293	cP	6200
Viscosity at 100 °C	ASTM D445	cSt	7,1
Viscosity index	ASTM D2270		140
Flash point COC	ASTM D92	°C	200
Pour point	ASTM D97	°C	-40
TBN	ASTM D4739	mgKOH/g	5,0
Sulphate ashes	ASTM D874	%	1,0

## Packaging

VOLUME	ART N°
5 L	0196
5 L (Tin can)	0175

TOR LUBRICANTS NORWAY  
Fjordalléen 16, 0250 Oslo, Norway  
Phone: +47 852 90054  
E-mail: info@nordkapp-oil.com

Information in this data sheet believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is given as a guide only. It is the responsibility of the user to evaluate and use products safely. No responsibility is taken for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. You should consult our local representative if you require any further information.