

Product data

Aves 0W-40

Performance Claims

SAE 0W-40 API SN/CF ACEA A3/B4

BMW Longlife-01 MB 229.3 VW 502.00 VW 505.00



Description

High-performance HC-Synthetic multigrade fuel-economy oil for diesel and petrol car engines. Specially selected HC-Synthetic base oils and highly effective long-term protective additives give this high-performance motor oil its excellent driving characteristics. The fuel economy leads to a reduction in CO2 emissions.

Advantages

- High wear protection at all operating conditions
- Excellent viscosity-temperature behavior
- Minimal frictional loss
- Very high cleaning capability
- Low volatilization loss
- High oxidation and temperature stability

Typical characteristics

PROPERTIES	METHOD	UNITS	TYPICAL INDICATORS
Density at 20°C	ASTM D1298	kg/m³	900
Viscosity at -35°C	ASTM D5293	сР	6200
Viscosity at 100°C	ASTM D445	cSt	13,5
Viscosity index	ASTM D2270		130
Flash point COC	ASTM D92	°C	180
Pour point	ASTM D97	°C	-30
TBN	ASTM D4739	mgKOH/g	5,5
Sulphate ashes	ASTM D874	%	1,5

Packaging

VOLUME	ART №
5 L	0091
5 L (Tin can)	0158
200 L	0092

TOR LUBRICANTS NORWAY Fjordalléen 16, 0250 Oslo, Norway Phone: +47 852 90054 E-mail: info@nordkapp-oil.com Information in this data sheet believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is given as a guide only. It is the responsibility of the user to evaluate and use products safely. No responsibility is taken for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. You should consult our local representative if you require any further information.