

# Aves 15W-40

## Performance Claims

SAE 15W-40

API SN/CF

ACEA A3/B4

VW 501.01/505.00; MB 229.1



## Description

Semi-synthetic motor oil with modern additives for gasoline and diesel engines in cars and vans. Suitable for all-season use in multi-valve engines, with or without turbocharging, and equipped with a catalyst.

## Advantages

- Optimum viscosity in various working conditions
- Excellent protection against wear and corrosion
- High thermo-oxidative stability
- Provides cleanliness and prevents the formation of deposits
- Provides long engine life

## Typical characteristics

PROPERTIES	METHOD	UNITS	TYPICAL INDICATORS
Density at 15°C	ASTM D1298	kg/m <sup>3</sup>	864
Viscosity at -20°C	ASTM D5293	cP	6780
Viscosity at 40°C	ASTM D445	cSt	95
Viscosity at 100°C	ASTM D445	cSt	14,5
Viscosity index	ASTM D2270		158
Flash point COC	ASTM D92	°C	222
Pour point	ASTM D97	°C	-33
TBN	ASTM D4739	mgKOH/g	9,9
Sulphate ashes	ASTM D874	%	1,29

## Packaging

VOLUME	ART №
1 L	0014
4 L	0015

TOR LUBRICANTS NORWAY  
Fjordalléen 16, 0250 Oslo, Norway  
Phone: +47 852 90054  
E-mail: info@nordkapp-oil.com

Information in this data sheet believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is given as a guide only. It is the responsibility of the user to evaluate and use products safely. No responsibility is taken for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. You should consult our local representative if you require any further information.