

Aves 20W-50

Performance Claims

SAE 20W-50
API SN/CF
ACEA A3/B4

VW 501.01 / 505.00; MB 229.1



Description

High-viscosity semi-synthetic motor oil based on mineral oils and synthetic components with a package of modern additives.

Advantages

- Best for use at high ambient temperatures
- Prevents sediment formation
- Excellent protection against wear and corrosion
- Low evaporation
- Provides long engine life

Typical characteristics

PROPERTIES	METHOD	UNITS	TYPICAL INDICATORS
Density at 15°C	ASTM D1298	kg/m ³	871
Viscosity at -15°C	ASTM D5293	cP	8200
Viscosity at 40°C	ASTM D445	cSt	137,6
Viscosity at 100°C	ASTM D445	cSt	18,6
Viscosity index	ASTM D2270		151
Flash point COC	ASTM D92	°C	232
Pour point	ASTM D97	°C	-28
TBN	ASTM D4739	mgKOH/g	9,7
Sulphate ashes	ASTM D874	%	1,27

Packaging

VOLUME	ART №
1 L	0016
4 L	0017

TOR LUBRICANTS NORWAY
Fjordalléen 16, 0250 Oslo, Norway
Phone: +47 852 90054
E-mail: info@nordkapp-oil.com

Information in this data sheet believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is given as a guide only. It is the responsibility of the user to evaluate and use products safely. No responsibility is taken for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. You should consult our local representative if you require any further information.