

Aves 5W-20

Performance Claims

SAE 5W-20
API SN/CF
ACEA A3/B4

TOYOTA; HONDA; FORD; VW 502.00, 505.00, 505.01; MB 229.31;
Opel GM-LL-A-025, GM-LL-B-025; Renault RN0700, RN0710



Description

Fuel economy synthetic engine oil. Developed for the latest gas and diesel engines of passenger cars and buses. Compatible with injector and multivalve engines, including those equipped with turbochargers, intercooler, and catalyst.

Advantages

- Guarantee efficient lubrication of the engine.
- High fuel economy effect.
- Ensures protection against sludging, coking, varnish and corrosion even under unfavorable operating conditions.
- Optimal energy saving and lifetime properties.
- Neutral towards sealing materials.
- Excellent low-temperature, anti-friction, anti-corrosion, detergent and antioxidant characteristics.

Typical characteristics

PROPERTIES	METHOD	UNITS	TYPICAL INDICATORS
Density at 20°C	ASTM D1298	kg/m ³	840
Viscosity index	ASTM D2270		167
Flash point COC	ASTM D92	°C	214
Pour point	ASTM D97	°C	-38
TBN	ASTM D4739	mgKOH/g	6,8

Packaging

VOLUME	ART №
1 L	0095
4 L	0096
5 L	0097

TOR LUBRICANTS NORWAY
Fjordalléen 16, 0250 Oslo, Norway
Phone: +47 852 90054
E-mail: info@nordkapp-oil.com

Information in this data sheet believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is given as a guide only. It is the responsibility of the user to evaluate and use products safely. No responsibility is taken for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. You should consult our local representative if you require any further information.