

Aves C2 0W-30

Performance Claims

SAE 0W-30
API SN/CF
ACEA C2

FIAT 9.55535-DS1, FIAT 9.55535-GS1, PSA B71 2290, PSA B71 2312, MB 229.61, BMW LONGLIFE-12 FE, CHRYSLER MS-13340, IVECO 18-1811 CLASSE SC1 LV, JAGUAR LAND ROVER STJLR.03.5007



Description

NORDKAPP AVES C2 SAE 0W-30 is a fully synthetic low-viscosity engine oil for passenger car gasoline and diesel engines with and without turbo-charging and direct injection. Provides a safe layer of lubrication at high operating temperatures and protects from corrosion and loss of oil through oxidation or coking. The excellent cold start behavior ensures optimum lubrication safety during cold running. It is optimally coordinated for prolonged drain intervals.

NORDKAPP AVES C2 SAE 0W-30 is especially suitable for use in automobile gasoline and diesel engines with subsequent exhaust treatment systems (DPF), which require engine oils with ACEA C2 specification, according to the OEM manual.

Advantages

- **Optimal protection for modern engines:** Protects against wear, corrosion, and deposits.
- **Enhanced fuel economy:** Reduces fuel consumption and emissions.
- **Excellent cold-start performance:** Ensures quick and reliable starts in cold weather.
- **Suitable for extended drain intervals:** Allows for longer oil change intervals.
- **Compatible with emission systems:** Specifically designed for vehicles with DPF and other emission control systems.

Typical characteristics

PROPERTIES	METHOD	UNITS	TYPICAL INDICATORS
Density at 20°C	ASTM D1298	kg/m ³	900
Viscosity at -35°C	ASTM D5293	cP	6200
Viscosity at 100°C	ASTM D445	cSt	10,9
Viscosity index	ASTM D2270		140
Flash point COC	ASTM D92	°C	200
Pour point	ASTM D97	°C	-38
TBN	ASTM D4739	mgKOH/g	5,0
Sulphate ashes	ASTM D874	%	0,8

Packaging

VOLUME	ART №
5 L	0131
5 L (Tin can)	0159