

Aves C3 0W-30

Performance Claims

SAE 0W-30
API SN/CF
ACEA C3

VW 504.00/507.00, MB 229.31, MB 229.51, PORSCHE C30, BMW
Longlife-04, Chrysler MS-11106



Description

NORDKAPP AVES C3 SAE 0W-30 is a fully synthetic fuel-efficient multigrade engine oil of the latest generation. The exceptional properties of these high-performance engine oils meet the current requirements and operating conditions of the mid-SAPS engine oils. Perfectly adapted to prolonged oil change intervals. The "Low Ash" (Mid SAPS) recipe protects the engine and catalytic converter system.

NORDKAPP AVES C3 SAE 0W-30 developed for pump-nozzle diesel engines without WIV-systems and light diesel engines from General Motors vehicles. Due to its special composition, this engine oil is perfectly suitable to meet several new OEM requirements. These properties additionally enable the use in gasoline and diesel engines both in salon cars and in transport vehicles with and without turbochargers.

Advantages

- Excellent engine cleanliness and performance
- Reduces fuel consumption
- Extended oil drain intervals (Longlife) DPF and ERG system long life due to low-ash formula
- Highest performance over the full temperature range

Typical characteristics

PROPERTIES	METHOD	UNITS	TYPICAL INDICATORS
Density at 20°C	ASTM D1298	kg/m ³	870
Viscosity at -35°C	ASTM D5293	cP	6200
Viscosity at 100°C	ASTM D445	cSt	10,9
Viscosity index	ASTM D2270		140
Flash point COC	ASTM D92	°C	200
Pour point	ASTM D97	°C	-40
TBN	ASTM D4739	mgKOH/g	5,0
Sulphate ashes	ASTM D874	%	1,0

Packaging

VOLUME	ART №
5 L	0169
5 L (Tin can)	0208
200 L	0170