

# Aves FS 5W-40

## Performance Claims

SAE 5W-40  
API SN/CF  
ACEA A3/B4

TOYOTA; HONDA; FORD; VW 502.00 / 505.00 / 505.01; MB 229.5;  
Opel GM-LL-A-025, GM-LL-B-025; Renault RN0700 / RN0710, BMW  
LONGLIFE-01, PORSCHE A40



## Description

Superior quality engine oil with a high content of additives ensures efficient operation of gasoline and diesel engines. Provides high anti-wear and energy-saving properties. Use in accordance with OEM recommendations.

## Advantages

- **Optimal engine protection:** Protects against wear, corrosion, and deposits.
- **Enhanced fuel efficiency:** Reduces fuel consumption.
- **Excellent low-temperature performance:** Ensures quick and reliable starts in cold weather.
- **Wide application range:** Suitable for a variety of gasoline and diesel engines.
- **Meets industry standards:** Complies with numerous international standards.

## Typical characteristics

PROPERTIES	METHOD	UNITS	TYPICAL INDICATORS
Density at 20 °C	ASTM D1298	kg/m <sup>3</sup>	910
Viscosity at -30 °C	ASTM D5293	cP	6600
Viscosity at 100 °C	ASTM D445	cSt	14,4
Viscosity index	ASTM D2270		140
Flash point COC	ASTM D92	°C	205
Pour point	ASTM D97	°C	-35
TBN	ASTM D4739	mgKOH/g	7,5
Sulphate ashes	ASTM D874	%	1,5

## Packaging

VOLUME	ART №
1 L	0188
5 L	0085
5 L (Tin can)	0117
200 L	0124

TOR LUBRICANTS NORWAY  
Fjordalléen 16, 0250 Oslo, Norway  
Phone: +47 852 90054  
E-mail: info@nordkapp-oil.com

Information in this data sheet believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is given as a guide only. It is the responsibility of the user to evaluate and use products safely. No responsibility is taken for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. You should consult our local representative if you require any further information.