

Aves LL 0W-20

Performance Claims

SAE 0W-20
API SN Plus
ACEA C5

ILSAC GF-5, MB 229.71, BMW Longlife -17FE+, VOLVO VCC
RBSO-2AE, Renault RN17 FE



Description

Fully synthetic low friction engine oil developed for modern engines of passenger cars with and without turbocharging and direct injection. Minimizes friction, wear, and fuel consumption and is suitable for extended drain intervals according to manufacturer's manual. The excellent cold start performance ensures efficient lubricant during start-up and provides a significant fuel-saving potential.

Advantages

- **Optimal fuel economy:** Minimizes friction and fuel consumption.
- **Extended drain intervals:** Allows for longer oil change intervals.
- **Superior wear protection:** Protects against wear and tear, extending engine life.
- **Excellent cold-start performance:** Ensures quick and reliable starts in cold weather.
- **High-performance formula:** Suitable for a wide range of modern engines.

Typical characteristics

PROPERTIES	METHOD	UNITS	TYPICAL INDICATORS
Density at 20°C	ASTM D1298	kg/m ³	900
Viscosity at -35°C	ASTM D5293	cP	6200
Viscosity at 100°C	ASTM D445	cSt	8,1
Viscosity index	ASTM D2270		140
Flash point COC	ASTM D92	°C	200
Pour point	ASTM D97	°C	-38
TBN	ASTM D4739	mgKOH/g	5,5
Sulphate ashes	ASTM D874	%	1,5

Packaging

VOLUME	ART №
5 L (Tin can)	0194

TOR LUBRICANTS NORWAY
Fjordalléen 16, 0250 Oslo, Norway
Phone: +47 852 90054
E-mail: info@nordkapp-oil.com

Information in this data sheet believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is given as a guide only. It is the responsibility of the user to evaluate and use products safely. No responsibility is taken for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. You should consult our local representative if you require any further information.