

Product data

Aves VR 5W-20

Performance Claims

SAE 5W-20 API SP

ILSAC GF-6A • Chrysler MS-6395 • Daihatsu • Fiat 9.55535-CR1 • Ford WSS-M2C 930-A • Ford WSS-M2C 945-A • Ford WSS-M2C 945-B1 • Ford WSS-M2C 960-A1 • GM 6094 M • GM dexos1 Gen 3 • Honda • Hyundai • Kia • Mazda • Mitsubishi • Mitsubishi Dia Queen • Nissan • Subaru • Toyota



Description

Aves VR 5W-20 is a high performance low-friction motor oil. Up-to-date formulation ensures that the motor oil is of low viscosity with a high shear stability and reliably prevents the formation of deposits, significantly reducing frictional losses in the engine and providing the optimum protection from wear. This results in fuel savings and an extended service life for the engine. Ideal for modern Asian and American gasoline engines with multi-valve technology and turbocharging with and without charge air cooling. For the protection and value retention of the engine during long intervals between oil changes and where there are extreme demands on the engine.

Advantages

- Exceptional Wear Protection: A high-quality formula reliably protects engine components from wear, even under the most extreme conditions.
- Optimal Fuel Economy: Low viscosity and high stability reduce frictional losses, which helps lower fuel consumption.
- Ideal for Modern Engines: Specifically developed for multi-valve, turbocharged gasoline engines in American and Asian vehicles.
- Extends Engine Life: Effectively prevents deposit formation and ensures engine cleanliness, increasing its service life.
- Extended Service Intervals: The oil's high stability allows for safely extending intervals between oil changes, according to manufacturer recommendations.

Typical characteristics

Packaging

VOLUME	ART №
1 L	0244
4 L	0245
5 L	0245



Product data

from hazards inherent in the nature of the material. You should consult our local representative if you require any further information.