

Branta HD 10W-40

Performance Claims

SAE 10W-40
API CF-4/SG
ACEA A3/B4, E7

MB 228.3; MB 229.1; VOLVO VDS-3; MACK EO-M PLUS / EO-N
RENAULT VI, RLD-2; MAN M 3275; CUMMINS CES;
20071/-72/-75/-76/-77/-78; MTU 2; IVECO; CATERPILLAR ECF-1-A,
ECF-2; ALLISON C-4; VOITH RETARDER TYP A



Description

Heavy Duty Improved Engine oil designed for modern diesel engines of minibuses and trucks, passenger cars including those working on high-sulfur fuel. It is made based on mineral oils and advanced additives.

Advantages

- Excellent lubricating, detergent and anti-corrosion properties
- Strong oil film protects the engine against wear and corrosion
- Reliable protection against low and high-temperature deposits
- Compatible with all types of seals
- Improved anti-foam properties

Typical characteristics

PROPERTIES	METHOD	UNITS	TYPICAL INDICATORS
Density at 15°C	ASTM D1298	kg/m ³	889
Viscosity at -25°C	ASTM D5293	cP	6700
Viscosity at 40°C	ASTM D445	cSt	116,3
Viscosity at 100°C	ASTM D445	cSt	14,9
Viscosity index	ASTM D2270		132
Flash point COC	ASTM D92	°C	225
Pour point	ASTM D97	°C	-32
TBN	ASTM D4739	mgKOH/g	8,9
Sulphate ashes	ASTM D874	%	1,23

Packaging

VOLUME	ART №
5 L	0051
20 L	0052
208 L	0053

TOR LUBRICANTS NORWAY
Fjordalléen 16, 0250 Oslo, Norway
Phone: +47 852 90054
E-mail: info@nordkapp-oil.com

Information in this data sheet believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is given as a guide only. It is the responsibility of the user to evaluate and use products safely. No responsibility is taken for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. You should consult our local representative if you require any further information.