

Branta HD 15W-40

Performance Claims

SAE 15W-40
API CF-4/SG
ACEA A3/B4, E7

MB 228.3, 229.1; MAN M 3275; VOLVO VDS-3; MACK EO-M PLUS;
CUMMINS CES 20071, 72, 76, 77, 78; MTU 2; IVECO; RENAULT RVI
RLD; CATERPILLAR ECF-1; ALLISON C-4; VOITH RETARDER TYP A



Description

Heavy Duty Improved Engine oil developed for a wide range of heavy-loaded engines, all-fleet engine oils for minibusses and trucks, and passenger cars including those working on high-sulfur fuel.

Advantages

- Excellent lubricating, detergent and anti-corrosion properties
- Strong oil film protects the engine against wear and corrosion
- Reliable protection against low and high-temperature deposits
- Compatible with all types of seals
- Improved anti-foam properties

Typical characteristics

PROPERTIES	METHOD	UNITS	TYPICAL INDICATORS
Density at 15°C	ASTM D1298	kg/m ³	882
Viscosity at -20°C	ASTM D5293	cP	6500
Viscosity at 40°C	ASTM D445	cSt	129,5
Viscosity at 100°C	ASTM D445	cSt	15,8
Viscosity index	ASTM D2270		129
Flash point COC	ASTM D92	°C	228
Pour point	ASTM D97	°C	-30
TBN	ASTM D4739	mgKOH/g	9,9
Sulphate ashes	ASTM D874	%	1,38

Packaging

VOLUME	ART №
5 L	0054
20 L	0055
208 L	0056

TOR LUBRICANTS NORWAY
Fjordalléen 16, 0250 Oslo, Norway
Phone: +47 852 90054
E-mail: info@nordkapp-oil.com

Information in this data sheet believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is given as a guide only. It is the responsibility of the user to evaluate and use products safely. No responsibility is taken for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. You should consult our local representative if you require any further information.