

# Corvus 4T 10W-40

## Performance Claims

SAE 10W-40  
API SL  
JASO MA-2

For all types and brands of 4-stroke engines: motorcycle, ATV, snowmobiles, lawn movers, generators, cultivators, other small machinery.



## Description

Semisynthetic engine oil for four-stroke motorcycle vehicles. Designed and suitable for year-round use in engines of motorcycles, scooters, and ATVs with any type of clutch, with air or liquid cooling system.

## Advantages

- Reliable wear protection during long load range
- High thermal stability
- Compatibility with elastomers
- Prevents the carbon formation

## Typical characteristics

PROPERTIES	METHOD	UNITS	TYPICAL INDICATORS
Density at 15°C	ASTM D1298	kg/m <sup>3</sup>	863
Viscosity at -25°C	ASTM D5293	cP	6500
Viscosity at 40°C	ASTM D445	cSt	118
Viscosity at 100°C	ASTM D445	cSt	17,4
Viscosity index	ASTM D2270		162
Flash point COC	ASTM D92	°C	226
Pour point	ASTM D97	°C	-36
TBN	ASTM D4739	mgKOH/g	6,6

## Packaging

VOLUME	ART №
1 L	0062

TOR LUBRICANTS NORWAY  
Fjordalléen 16, 0250 Oslo, Norway  
Phone: +47 852 90054  
E-mail: [info@nordkapp-oil.com](mailto:info@nordkapp-oil.com)

Information in this data sheet believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is given as a guide only. It is the responsibility of the user to evaluate and use products safely. No responsibility is taken for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. You should consult our local representative if you require any further information.