

# Flushing oil

## Performance Claims



## Description

Superior quality flushing oil with a high content of additives ensures efficient flushing of gasoline and diesel engines. Provides high dispersant and detergent properties.

## Advantages

- 1) Drain the used oil, empty (if possible) the oil filter.
- 2) Close the drain plug, return the oil filter to its place, fill in flushing oil.
- 3) Let the engine run at idle speed during 15 min.
- 4) Stop the engine.
- 5) Drain the flushing oil, remove an old oil filter.
- 6) Install a new oil filter and fill in the new engine oil.

## Typical characteristics

## Packaging

**VOLUME**  
3.5 L

**ART No**  
0138

TOR LUBRICANTS NORWAY  
Fjordalléen 16, 0250 Oslo, Norway  
Phone: +47 852 90054  
E-mail: [info@nordkapp-oil.com](mailto:info@nordkapp-oil.com)

Information in this data sheet believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is given as a guide only. It is the responsibility of the user to evaluate and use products safely. No responsibility is taken for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. You should consult our local representative if you require any further information.