

# Larus 15W-40

## Performance Claims

SAE 15W-40

API SL/CF

ACEA A3/B4

MB 228.1, 229.1; VW 505.00; VOLVO VDS;

MAN 271; MTU



## Description

Semi-synthetic engine oil based on mineral oils and synthetic components. It is applied to multi-valve gasoline and diesel engines of passenger cars and light commercial vehicles, with or without turbocharging, equipped with catalysts.

## Advantages

- Multipurpose usage
- Good viscosity/temperature properties
- Prevention of deposit formation
- Excellent elastomer compatibility
- Reliable antiwear properties during the whole operation period

## Typical characteristics

| PROPERTIES         | METHOD     | UNITS             | TYPICAL INDICATORS |
|--------------------|------------|-------------------|--------------------|
| Density at 15°C    | ASTM D1298 | kg/m <sup>3</sup> | 872                |
| Viscosity at -20°C | ASTM D5293 | cP                | 5800               |
| Viscosity at 40°C  | ASTM D445  | cSt               | 122                |
| Viscosity at 100°C | ASTM D445  | cSt               | 14,5               |
| Viscosity index    | ASTM D2270 |                   | 135                |
| Flash point COC    | ASTM D92   | °C                | 224                |
| Pour point         | ASTM D97   | °C                | -33                |
| TBN                | ASTM D4739 |                   | 9,2                |
| Sulphate ashes     | ASTM D874  | %                 | 1,34               |

## Packaging

| VOLUME | ART № |
|--------|-------|
| 1 L    | 0023  |
| 4 L    | 0024  |

TOR LUBRICANTS NORWAY  
Fjordalléen 16, 0250 Oslo, Norway  
Phone: +47 852 90054  
E-mail: info@nordkapp-oil.com

Information in this data sheet believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is given as a guide only. It is the responsibility of the user to evaluate and use products safely. No responsibility is taken for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. You should consult our local representative if you require any further information.