

# Larus DIESEL 15W-40

## Performance Claims

SAE 15W-40

API CF

ACEA A3/B4

MB 228.3, MB 229.1; VW 501.01/505.00



## Description

Semi-synthetic engine oil for diesel engines of passenger and light-duty commercial vehicles. Intended for multi-valve engines of passenger cars and vans with direct injection (including common rail technology), with and without turbo-charging, equipped with catalyst.

## Advantages

- Optimized viscosity at high temperatures
- Optimum engine cleanliness
- Oxidation and thermal stability
- Excellent antiwear properties
- Ensures long lifetime mileage

## Typical characteristics

PROPERTIES	METHOD	UNITS	TYPICAL INDICATORS
Density at 15°C	ASTM D1298	kg/m <sup>3</sup>	881
Viscosity at -20°C	ASTM D5293	cP	6200
Viscosity at 100°C	ASTM D445	cSt	15,2
Viscosity index	ASTM D2270		156
Flash point COC	ASTM D92	°C	226
Pour point	ASTM D97	°C	-34
TBN	ASTM D4739	mgKOH/g	9,5
Sulphate ashes	ASTM D874	%	1,41

## Packaging

VOLUME	ART №
1 L	0035
4 L	0036
5 L	0037

TOR LUBRICANTS NORWAY  
Fjordalléen 16, 0250 Oslo, Norway  
E-mail: [info@nordkapp-oil.com](mailto:info@nordkapp-oil.com)

Information in this data sheet believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is given as a guide only. It is the responsibility of the user to evaluate and use products safely. No responsibility is taken for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. You should consult our local representative if you require any further information.