

NETTA EP2

Performance Claims

NLGI 2 · LB/GC

NLGI 2 · KP2P-30 · L-XCEHB 2 · LB/GC



Description

Recommended for lubricating various friction units, including rolling and sliding bearings, hinges, rails, gears, and other equipment components. Particularly suitable for industrial equipment operating in harsh conditions and requiring EP (extreme pressure) lubricants, as well as equipment prone to moisture.

Advantages

- Reduced wear under high loads and vibration;
- Provides excellent protection against rust and corrosion;
- Resistant to water washout;
- Provides high reliability of equipment;
- Increases the life of bearings in wet environments.

Typical characteristics

PROPERTIES	UNITS	TYPICAL INDICATORS
Viscosity at 40°C	mm ² /s	221
Penetration at 25°C	10 ⁻¹ ·mm	285
Dropping point	°C	270
Corrosion impact		withstands
Tribological Characteristics on a 4-ball machine	kg	235
Color		blue

Packaging

VOLUME
0,4 kg

ART №:
0137

TOR LUBRICANTS NORWAY
Fjordalléen 16, 0250 Oslo, Norway
Phone: +47 852 90054
E-mail: info@nordkapp-oil.com

Information in this data sheet believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is given as a guide only. It is the responsibility of the user to evaluate and use products safely. No responsibility is taken for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. You should consult our local representative if you require any further information.