

Product data

ORANGE ANTIFREEZE + COOLANT Ready for use G12

Performance Claims

VW, Audi, Seat, Skoda TL 774-D (G12), Opel/GM 6277M (+B040 1065), MAN 324 Type SNF, MB 325.3, Porsche, Scania, Ford WSS M97B44-D, General Motors, Chrysler, Dodge, Jeep, Ford, Lincoln, Toyota, Mazda, Nissan, Acura, Lexus, Detroit Diesel, PSA, Deutz, BS 6580, ASTM D3306/D4656/D4985, JASO M325, NATO S-759



Description

High-quality coolant for modern gasoline and diesel engines (including engines made of light metals), operating in a variety of climatic and seasonal conditions.

Advantages

- Highly efficient and durable corrosion protection for all cooling system components, especially aluminum ones;
- Protection against freezing and overheating;
- Protection against corrosion and cavitation;
- Non-aggressive for lacquer, flexible tubes and seals;
- Corresponds to the best liquid analogues of the G12 class in the world;
- Excellent performance up to 250,000 km.

Typical characteristics

Packaging

	VOLUME	ART №
- 1	4 L	0141
٠,		Y

TOR LUBRICANTS NORWAY Fjordalléen 16, 0250 Oslo, Norway Phone: +47 852 90054 E-mail: info@nordkapp-oil.com Information in this data sheet believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is given as a guide only. It is the responsibility of the user to evaluate and use products safely. No responsibility is taken for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. You should consult our local representative if you require any further information.