

PSF

Performance Claims

PSF

GM DEXRON IID | FORD MERCON | VW G 002 00, G 004 000, G 002 012 | Chrysler MS-1872, MS-5931, MS-9602, MS-10838, MS-11655 | Ford M2C 195-A, M2C 204-A(2)GM 88901975, 89021184, 9985010, 9985835 | Hyundai/Kia PSF-3, PSF-4 | MB 236.3, 345.0 | Mitsubishi PS Fluid, SP III | Nissan PS-II | CHF 7.1, 11S, 202 | Saab 30 09 800, 30 32 380 | Subaru K0209A0080 | Toyota PSF-EH | Volvo 1161529 | MAN M 3289 | BMW 81229407758, 82111468041 | Opel 1940715, 1940766 | PSA S 71 2710 | GM/Saab Cold Climate Power Steering Fluid.

Description

Multigrade, highly efficient power fluid ensures excellent anti-friction and extreme pressure properties. Protects the mechanisms' details from negative factors during heavy-duty conditions, reduces the level of energy losses in friction, noise decrease, vibration, and shock load.

Advantages

- **Smooth and quiet steering:** Reduces steering effort and noise.
- **Excellent low-temperature performance:** Ensures smooth steering even in cold weather.
- **Superior wear protection:** Protects steering system components from wear and tear.
- **Enhanced system stability:** Improves steering response and stability.
- **Wide compatibility:** Suitable for a wide range of vehicles and steering systems.

Typical characteristics

PROPERTIES	METHOD	UNITS	TYPICAL INDICATORS
Density at 20°C	ASTM D1298	kg/m ³	879
Viscosity at 100°C	ASTM D445	cSt	7,5
Viscosity index	ASTM D2270		117
Flash point COC	ASTM D92	°C	185
Pour point	ASTM D97	°C	-40

Packaging

VOLUME	ART №
1 L	0135

TOR LUBRICANTS NORWAY
Fjordalléen 16, 0250 Oslo, Norway
E-mail: info@nordkapp-oil.com

Information in this data sheet believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is given as a guide only. It is the responsibility of the user to evaluate and use products safely. No responsibility is taken for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. You should consult our local representative if you require any further information.