

Spinus 2T

Performance Claims

API TC
JASO FC

For all types and brands of 2-stroke engines. Increase power-to-weight ratio of small-capacity motorcycles, mopeds, scooters, tuk-tuks, karts, chainsaws, grass and garden trimmers.



Description

Semisynthetic engine oil for air-cooled two-stroke motorcycle engines. Intended for use in engines of motorcycles, scooters, park and gardening equipment.

Advantages

- High lubricating ability
- Wear protection
- Stability at high temperatures
- Thermal oxidation stability
- Low ash content

Typical characteristics

PROPERTIES	METHOD	UNITS	TYPICAL INDICATORS
Density at 15°C	ASTM D1298	kg/m ³	864
Viscosity at 40°C	ASTM D5293	cSt	46,2
Viscosity at 100°C	ASTM D445	cSt	8
Viscosity index	ASTM D2270		145
Flash point COC	ASTM D92	°C	116
Pour point	ASTM D97	°C	-25
TBN	ASTM D4739	mgKOH/g	1,4
Sulphate ashes	ASTM D874	%	0,14

Packaging

VOLUME	ART №
1 L	0064

TOR LUBRICANTS NORWAY
Fjordalléen 16, 0250 Oslo, Norway
Phone: +47 852 90054
E-mail: info@nordkapp-oil.com

Information in this data sheet believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is given as a guide only. It is the responsibility of the user to evaluate and use products safely. No responsibility is taken for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. You should consult our local representative if you require any further information.