

TETRIX 75W-85

Performance Claims

SAE 75W-85
API GL-4, MT-1

API GL-4; API MT-1; MIL L 2105; MB 235.16, MB 235.31, MB 235.4,
MB 235.5 VW/Audi G 052 190 , VW/Audi G 055 190



Description

Semisynthetic transmission oil for manual gears. Complies with viscosity grade SAE 75W-85. Synthetic components allow to use it in heavy-duty components, drive axle gearboxes, and steering units, where EP API GL-4 is required.

Advantages

- **Superior protection:** Provides exceptional wear protection for your transmission.
- **Versatile performance:** Suitable for a wide range of manual transmissions.
- **Reliable in all conditions:** Ensures smooth operation in all weather conditions.
- **Industry-approved quality:** Meets or exceeds international standards.
- **Extended lifespan:** Prolongs the life of your transmission.

Typical characteristics

PROPERTIES	METHOD	UNITS	TYPICAL INDICATORS
Density at 15°C	ASTM D1298	kg/m ³	875
Viscosity at 40°C	ASTM D5293	cSt	80
Viscosity at 100°C	ASTM D445	cSt	12,8
Viscosity index	ASTM D2270		160
Flash point COC	ASTM D92	°C	220
Pour point	ASTM D97	°C	-45

Packaging

VOLUME	ART N ^o
1 L	0140

TOR LUBRICANTS NORWAY
Fjordalléen 16, 0250 Oslo, Norway
Phone: +47 852 90054
E-mail: info@nordkapp-oil.com

Information in this data sheet believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is given as a guide only. It is the responsibility of the user to evaluate and use products safely. No responsibility is taken for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. You should consult our local representative if you require any further information.