

# Tetrix 75W-90

## Performance Claims

SAE 75W-90  
API GL-4

MAN 341 Z-1; MB 235.1; ZF TE-ML 02A, 16A, 17A, 19A;  
MIL-L-2105 D



## Description

Semi-synthetic transmission oil for manual gears. Complies with viscosity grade SAE 75W-90. Synthetic components allow for use in heavy-duty components, drive axle gearboxes, and steering units, where EP API GL-4 is required.

## Advantages

- Excellent anti-wear and corrosion protection
- Excellent high temperature characteristics
- High load-bearing ability and oxidation stability
- Good viscosity properties during the whole operation period

## Typical characteristics

PROPERTIES	METHOD	UNITS	TYPICAL INDICATORS
Density at 15°C	ASTM D1298	kg/m <sup>3</sup>	875
Viscosity at 40°C	ASTM D5293	cSt	82
Viscosity at 100°C	ASTM D445	cSt	14,3
Viscosity index	ASTM D2270		185
Flash point COC	ASTM D92	°C	230
Pour point	ASTM D97	°C	-45

## Packaging

VOLUME	ART №
1 L	0066

TOR LUBRICANTS NORWAY  
Fjordalléen 16, 0250 Oslo, Norway  
Phone: +47 852 90054  
E-mail: info@nordkapp-oil.com

Information in this data sheet believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is given as a guide only. It is the responsibility of the user to evaluate and use products safely. No responsibility is taken for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. You should consult our local representative if you require any further information.