

Tetrix 80W-90

Performance Claims

SAE 80W-90
API GL-4

MB 235.0; MACK GO-J; MAN 341 Type Z2 / E2; 3343 Type M, 342 Type M2; MF 1134; SCANIA STO 1: 0, 2: 0; VOLVO 97310, 97312; ZF TE-ML; MIL PRF-2105 E/L 2105 A, B, C, D, E



Description

Mineral transmission oil for manual gears operating under heavy-duty conditions and low temperatures. Intended for modern gears, differential drives, torque dividers, hypoid gears of back axle, which require transmission oil of API GL-4 level with high content of antiwear additives, according to OEM specifications.

Advantages

- Excellent oil flow at low temperatures
- Excellent antiwear and corrosion protection
- Oxidation stability
- Excellent viscosity-temperature properties
- Consistent with elastomeric materials

Typical characteristics

PROPERTIES	METHOD	UNITS	TYPICAL INDICATORS
Density at 15°C	ASTM D1298	kg/m ³	882
Viscosity at 40°C	ASTM D5293	cSt	126
Viscosity at 100°C	ASTM D445	cSt	15
Viscosity index	ASTM D2270		121
Flash point COC	ASTM D92	°C	232
Pour point	ASTM D97	°C	-30

Packaging

VOLUME	ART №
1 L	0068

TOR LUBRICANTS NORWAY
Fjordalléen 16, 0250 Oslo, Norway
Phone: +47 852 90054
E-mail: info@nordkapp-oil.com

Information in this data sheet believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is given as a guide only. It is the responsibility of the user to evaluate and use products safely. No responsibility is taken for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. You should consult our local representative if you require any further information.