

Tetrix HD 75W-90

Performance Claims

SAE 75W-90

API GL-5

MAN 341 Z-1 | MB 235.1 | ZF TE-ML 02A, 16A, 17A, 19A | MIL-L-2105 D



Description

Synthetic transmission oil for manual gears. Intended for year-round use for lubrication of mechanical gears of passenger cars and trucks. Considered to be used in heavy-duty units of construction and agricultural machinery and devices where they require using oils of GL-5 class.

Advantages

- High oxidation stability
- Excellent corrosion protection
- Low pour point
- Excellent extreme pressure properties
- High-repeatability viscosity index

Typical characteristics

PROPERTIES	METHOD	UNITS	TYPICAL INDICATORS
Density at 15°C	ASTM D1298	kg/m ³	869
Viscosity at 40°C	ASTM D5293	cSt	102
Viscosity at 100°C	ASTM D445	cSt	15
Viscosity index	ASTM D2270		161
Flash point COC	ASTM D92	°C	202
Pour point	ASTM D97	°C	-45

Packaging

VOLUME	ART №
1 L	0070

TOR LUBRICANTS NORWAY
Fjordalléen 16, 0250 Oslo, Norway
Phone: +47 852 90054
E-mail: info@nordkapp-oil.com

Information in this data sheet believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is given as a guide only. It is the responsibility of the user to evaluate and use products safely. No responsibility is taken for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. You should consult our local representative if you require any further information.