

# Xenus 10W-40

## Performance Claims

SAE 10W-40

API SG/CD

ACEA A3/B3

VW 501.01/505.00; MB 229.1



## Description

Multi-grade semi-synthetic engine oil for passenger and light-duty commercial vehicles. Intended for retro-cars where engine oil with API SG/CD, ACEA A3/B3 quality level is required.

## Advantages

- Year-round use
- Excellent cold-starting properties
- Protection from sediments and corrosion formation
- Low volatilization loss at high operational temperatures
- Steady oil pressure in the lubrication system

## Typical characteristics

PROPERTIES	METHOD	UNITS	TYPICAL INDICATORS
Density at 15°C	ASTM D1298	kg/m <sup>3</sup>	868
Viscosity at -25°C	ASTM D5293	cP	6420
Viscosity at 40°C	ASTM D445	cSt	95,43
Viscosity at 100°C	ASTM D445	cSt	13,92
Viscosity index	ASTM D2270		148
Flash point COC	ASTM D92	°C	224
Pour point	ASTM D97	°C	-36
TBN	ASTM D4739	mgKOH/g	7,3
Sulphate ashes	ASTM D874	%	1,03

## Packaging

VOLUME	ART №
1 L	0038
4 L	0039
5 L	0040

TOR LUBRICANTS NORWAY  
Fjordalléen 16, 0250 Oslo, Norway  
Phone: +47 852 90054  
E-mail: info@nordkapp-oil.com

Information in this data sheet believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is given as a guide only. It is the responsibility of the user to evaluate and use products safely. No responsibility is taken for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. You should consult our local representative if you require any further information.