

Xenus 15W-40

Performance Claims

SAE 15W-40
API SG/CD
ACEA A3/B3

MB 229.1; VW 501.00



Description

Mineral engine oil, for all-season use in gasoline and diesel engines of passenger cars and lightweight commercial vehicles. Recommended for use in retro cars or new cars, where they advise using engine oil of quality degree API SG/CD, ACEA A3/B3.

Advantages

- All season use
- Good stability
- Protection from stratum and corrosion
- Low evaporation at high operating temperatures
- Stable pressure in the lubrication system

Typical characteristics

PROPERTIES	METHOD	UNITS	TYPICAL INDICATORS
Density at 15°C	ASTM D1298	kg/m ³	869
Viscosity at -20°C	ASTM D5293	cP	6368
Viscosity at 40°C	ASTM D445	cSt	105,5
Viscosity at 100°C	ASTM D445	cSt	13,91
Viscosity index	ASTM D2270		132
Flash point COC	ASTM D92	°C	230
Pour point	ASTM D97	°C	-35
TBN	ASTM D4739	mgKOH/g	7,1
Sulphate ashes	ASTM D874	%	0,98

Packaging

VOLUME	ART №
1 L	0041
5 L	0042
20 L	0043

TOR LUBRICANTS NORWAY
Fjordalléen 16, 0250 Oslo, Norway
Phone: +47 852 90054
E-mail: info@nordkapp-oil.com

Information in this data sheet believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is given as a guide only. It is the responsibility of the user to evaluate and use products safely. No responsibility is taken for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. You should consult our local representative if you require any further information.